



DutchWalltextile Co.

## DWC Colforte – Technical Data Sheet

### *Special features*

DWC Colforte is a high viscosity adhesive for wallcovering applications.

The adhesive should only be used on sealed surfaces (which are completely non-absorbent) such as synthetics, painted surfaces and pre-treated or galvanised metal.

The adhesive can be used for textile and vinyl wallcoverings, and is especially suited for heavy weight wallcoverings.

### *Technical data*

|                      |  |
|----------------------|--|
| Composition          | : paste based on synthetic resin dispersion  |
| Brookfield viscosity | : 37.500 mPa.s (HAT; spindle 6; 20rpm; 20°C) |
| Solid content        | : 64%  |
| pH                   | : 7,5  |
| Open time            | : 15 – 45 minutes                            |
| Setting speed        | : 1 – 4 hours                                |
| Consumption          | : approx. 150 – 400 gr/m <sup>2</sup>        |
| Colour               | : cream                                      |

Open time, setting speed and consumption are depending on the substrates to be bonded, room temperature and humidity.

### *Method of application*

DWC Colforte is ready for use.

Apply the adhesive with a short-haired synthetic roller.

The surface must be clean, dry, smooth and solid.

### *Cleaning*

Cleaning can be performed with water.

### *Packaging*

DWC Colforte is available in 3 sizes: 2 ltr – 5 ltr – 10 ltr.

### *Storage*

Keep the container closed, and store preferably at room temperature.

The adhesive is frost-proof to -10°C.

Shelf life is 9 months.

